

Allen-Bradley FLEX I/O and FLEX I/O-XT (Bulletin 1794), catalog number list

56 catalog numbers for Allen-Bradley FLEX I/O and FLEX I/O-XT (Bulletin 1794) adapters, power supplies, I/O modules and terminal bases, with the key ratings from the official Rockwell selection guide. XT marks the extended temperature version; K marks a conformally coated version. Each I/O module needs a terminal base unit, which is ordered separately. Ask us for availability, lead time and price for any item below.

Communication adapters

ORDER NUMBER	DESCRIPTION	
1794-ACN15	ControlNet adapter, 5 Mbps, up to 8 FLEX I/O modules (nonredundant media)	Request a Quote
1794-ACNR15	ControlNet adapter for redundant media, 5 Mbps, up to 8 FLEX I/O modules	Request a Quote
1794-ACNR15XT	ControlNet adapter for redundant media, 5 Mbps, extended temperature -25...+70 °C	Request a Quote
1794-AENT	EtherNet/IP adapter, 1 RJ45 port, 10/100 Mbps, up to 8 FLEX I/O modules	Request a Quote
1794-AENTR	EtherNet/IP adapter, 2 RJ45 ports (DLR), 10/100 Mbps, up to 8 FLEX I/O modules	Request a Quote
1794-AENTRXT	EtherNet/IP adapter, 2 RJ45 ports (DLR), extended temperature -25...+70 °C	Request a Quote
1794-ASB	Remote I/O adapter, 57.6/115.2/230.4 Kbps, up to 8 FLEX I/O modules	Request a Quote

Power supplies

ORDER NUMBER	DESCRIPTION	
1794-PS13	Power supply, 120V/220V AC input, 24V DC output, 1.3 A	Request a Quote
1794-PS3	Power supply, 120V/220V AC input, 24V DC output, 3.0 A	Request a Quote

Digital and relay I/O modules

ORDER NUMBER	DESCRIPTION	
1794-IA16	16 inputs, 120V AC, nonisolated	Request a Quote
1794-IB10X0B6	10 sinking inputs + 6 sourcing outputs, 24V DC	Request a Quote
1794-IB16	16 sinking inputs, 24V DC	Request a Quote
1794-IB16D	16 diagnostic inputs, 24V DC	Request a Quote
1794-IB16X0B16P	16 inputs + 16 protected outputs, 24V DC	Request a Quote
1794-IB16XT	16 sinking inputs, 24V DC, extended temperature	Request a Quote
1794-IB32	32 sinking inputs, 24V DC, in groups	Request a Quote
1794-IM16	16 inputs, 240V AC, nonisolated	Request a Quote

ORDER NUMBER	DESCRIPTION	
1794-IV16	16 sourcing inputs, 24V DC	Request a Quote
1794-0A16	16 outputs, 120V AC, nonisolated	Request a Quote
1794-0A8	8 outputs, 120V AC, nonisolated	Request a Quote
1794-0B16	16 sourcing outputs, 24V DC	Request a Quote
1794-0B16P	16 protected sourcing outputs, 24V DC, 8 A per module	Request a Quote
1794-0B16PXT	16 protected sourcing outputs, 24V DC, extended temperature	Request a Quote
1794-0B32P	32 protected sourcing outputs, 24V DC, in groups, 14 A per module	Request a Quote
1794-0B8	8 sourcing outputs, 24V DC	Request a Quote
1794-0B8EPXT	8 protected sourcing outputs, 24V DC, 10 A per module, extended temperature	Request a Quote
1794-0M16	16 outputs, 240V AC, nonisolated	Request a Quote
1794-0V32	32 sinking outputs, 24V DC, in groups	Request a Quote
1794-0W8	8 isolated relay outputs, 2.0 A @ 125V AC resistive	Request a Quote
1794-0W8XT	8 isolated relay outputs, extended temperature -20...+70 °C	Request a Quote

Analog, temperature and counter modules

ORDER NUMBER	DESCRIPTION	
1794-IE12	12 analog inputs, 4...20 mA / 0...20 mA or $\pm 10V$	Request a Quote
1794-IE4X0E2	4 analog inputs + 2 analog outputs, 4...20 mA, 0...20 mA, $\pm 10V$, 0...10V	Request a Quote
1794-IE4X0E2XT	4 analog inputs + 2 analog outputs, extended temperature -20...+70 °C	Request a Quote
1794-IE8	8 single-ended analog inputs, 4...20 mA, 0...20 mA, $\pm 10V$, 0...10V, 12 bits	Request a Quote
1794-IE8XT	8 single-ended analog inputs, extended temperature -20...+70 °C	Request a Quote
1794-IF4I	4 isolated analog inputs, 4...20 mA, 0...20 mA, ± 20 mA, $\pm 10V$, 0...10V, $\pm 5V$, 0...5V	Request a Quote
1794-IF8IH	8 isolated HART analog inputs, 4...20 mA / 0...20 mA, 16 bits	Request a Quote
1794-IR8	8 RTD inputs, 2- and 3-wire, 16 bits across 435 Ω	Request a Quote
1794-IRT8	8 thermocouple/RTD/mV inputs, 14 bits	Request a Quote
1794-IRT8XT	8 thermocouple/RTD/mV inputs, extended temperature -20...+70 °C	Request a Quote
1794-0E12	12 analog outputs, 0...20 mA or $\pm 10V$	Request a Quote
1794-0E4	4 analog outputs, 4...20 mA, 0...20 mA, $\pm 10V$, 0...10V, 12 bits + sign	Request a Quote
1794-0E4XT	4 analog outputs, extended temperature -20...+70 °C	Request a Quote
1794-0F4I	4 isolated analog outputs, 4...20 mA, 0...20 mA, $\pm 10V$, 0...10V, $\pm 5V$, 0...5V, 15 bits + sign	Request a Quote
1794-0F8IH	8 isolated HART analog outputs, 4...20 mA / 0...20 mA, 16 bits	Request a Quote

Specialty modules

ORDER NUMBER	DESCRIPTION	
1794-VHSC	Very high-speed counter, 2 channels of A/B/Z quadrature inputs, 2 outputs	Request a Quote

Terminal bases and accessories

ORDER NUMBER	DESCRIPTION	
1794-CE3	Extender cable, 0.9 m (3 ft)	Request a Quote
1794-TB2	Terminal base, cage clamp, 2-wire: 16 I/O, 18 common, 2 +V	Request a Quote
1794-TB3	Terminal base, cage clamp, 3-wire: 16 I/O, 18 common, 18 +V	Request a Quote
1794-TB32	Terminal base, cage clamp, 32 I/O, 8 common, 8 +V	Request a Quote
1794-TB3G	Terminal base, grounded screw clamp, for analog modules	Request a Quote
1794-TB3S	Terminal base, spring clamp, 3-wire: 16 I/O, 18 common, 18 +V	Request a Quote
1794-TB3SK	Terminal base, spring clamp, 3-wire, conformal coated	Request a Quote
1794-TB3T	Temperature terminal base, cage clamp, 2 sets of CJC	Request a Quote
1794-TBN	Terminal base, NEMA-style screw clamp with cover: 16 I/O, 2 common, 2 +V	Request a Quote
1794-TBNF	Terminal base, fused NEMA-style screw clamp, eight 5 x 20 mm fuses	Request a Quote

Prepared by GEARWELL, 2026-10-14. Allen-Bradley, FLEX, FLEX I/O, ControlLogix, CompactLogix and Rockwell Automation are trademarks of Rockwell Automation, Inc. GEARWELL is an independent supplier and is not affiliated with or authorized by Rockwell Automation. Catalog numbers, ratings and specifications are taken from FLEX I/O and FLEX I/O-XT Selection Guide, Rockwell Automation publication 1794-SG002I-EN-P (April 2024). They are given for identification; confirm the full catalog number with the product label before ordering. Official documentation: literature.rockwellautomation.com.