

Allen-Bradley PowerFlex 40 AC drives (22B) and options, catalog number list

94 catalog numbers for Allen-Bradley PowerFlex 40 AC drives and their communication, HIM and cover options, from the official product selection table. Each drive row gives kW, HP, output current, input voltage and enclosure. Catalog number: position 5 = voltage (V 120 V 1-phase, A 240 V 1-phase, B 240 V 3-phase, D 480 V 3-phase, E 600 V 3-phase); positions 6...8 = output current; position 9 = enclosure (N IP20 panel mount, F IP20 flange mount, C IP66 NEMA/UL Type 4X/12); position 11 = EMC filter (0 none, 1 filtered); position 12 = brake IGBT (3 without, 4 with). Ask us for availability, lead time and price for any item below.

100...120 V AC, 1-phase input

ORDER NUMBER	DESCRIPTION	
22B-V2P3C104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 100...120 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-V2P3F104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 100...120 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-V2P3N104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 100...120 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote
22B-V5P0C104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 100...120 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-V5P0F104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 100...120 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-V5P0N104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 100...120 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote
22B-V6P0C104	PowerFlex 40, 1.1 kW (1.5 HP), 6.0 A, 100...120 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-V6P0F104	PowerFlex 40, 1.1 kW (1.5 HP), 6.0 A, 100...120 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-V6P0N104	PowerFlex 40, 1.1 kW (1.5 HP), 6.0 A, 100...120 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote

200...240 V AC, 1-phase input

ORDER NUMBER	DESCRIPTION	
22B-A2P3N114	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 1-phase input, IP20 panel mount, integral EMC filter, frame B	Request a Quote
22B-A5P0N114	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 1-phase input, IP20 panel mount, integral EMC filter, frame B	Request a Quote
22B-A8P0N114	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 1-phase input, IP20 panel mount, integral EMC filter, frame B	Request a Quote
22B-A012N114	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 1-phase input, IP20 panel mount, integral EMC filter, frame C	Request a Quote

ORDER NUMBER	DESCRIPTION	
22B-A2P3C104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-A2P3F104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-A2P3N104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote
22B-A5P0C104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-A5P0F104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-A5P0N104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote
22B-A8P0C104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 1-phase input, IP66 NEMA 4X/12	Request a Quote
22B-A8P0F104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-A8P0N104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 1-phase input, IP20 panel mount, frame B	Request a Quote
22B-A012F104	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 1-phase input, IP20 flange mount	Request a Quote
22B-A012N104	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 1-phase input, IP20 panel mount, frame C	Request a Quote

200...240 V AC, 3-phase input

ORDER NUMBER	DESCRIPTION	
22B-B2P3C104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-B2P3F104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B2P3N104	PowerFlex 40, 0.4 kW (0.5 HP), 2.3 A, 200...240 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-B5P0C104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-B5P0F104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B5P0N104	PowerFlex 40, 0.75 kW (1.0 HP), 5.0 A, 200...240 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-B8P0C104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-B8P0F104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote

ORDER NUMBER	DESCRIPTION	
22B-B8P0N104	PowerFlex 40, 1.5 kW (2.0 HP), 8.0 A, 200...240 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-B012C104	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-B012F104	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B012N104	PowerFlex 40, 2.2 kW (3.0 HP), 12.0 A, 200...240 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-B017C104	PowerFlex 40, 3.7 kW (5.0 HP), 17.5 A, 200...240 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-B017F104	PowerFlex 40, 3.7 kW (5.0 HP), 17.5 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B017N104	PowerFlex 40, 3.7 kW (5.0 HP), 17.5 A, 200...240 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-B024F104	PowerFlex 40, 5.5 kW (7.5 HP), 24.0 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B024N104	PowerFlex 40, 5.5 kW (7.5 HP), 24.0 A, 200...240 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote
22B-B033F104	PowerFlex 40, 7.5 kW (10.0 HP), 33.0 A, 200...240 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-B033N104	PowerFlex 40, 7.5 kW (10.0 HP), 33.0 A, 200...240 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote

380...480 V AC, 3-phase input

ORDER NUMBER	DESCRIPTION	
22B-D1P4C104	PowerFlex 40, 0.4 kW (0.5 HP), 1.4 A, 380...480 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-D1P4F104	PowerFlex 40, 0.4 kW (0.5 HP), 1.4 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D1P4N104	PowerFlex 40, 0.4 kW (0.5 HP), 1.4 A, 380...480 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-D2P3C104	PowerFlex 40, 0.75 kW (1.0 HP), 2.3 A, 380...480 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-D2P3F104	PowerFlex 40, 0.75 kW (1.0 HP), 2.3 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D2P3N104	PowerFlex 40, 0.75 kW (1.0 HP), 2.3 A, 380...480 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-D4P0C104	PowerFlex 40, 1.5 kW (2.0 HP), 4.0 A, 380...480 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-D4P0F104	PowerFlex 40, 1.5 kW (2.0 HP), 4.0 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote

ORDER NUMBER	DESCRIPTION	
22B-D4P0N104	PowerFlex 40, 1.5 kW (2.0 HP), 4.0 A, 380...480 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-D6P0C104	PowerFlex 40, 2.2 kW (3.0 HP), 6.0 A, 380...480 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-D6P0F104	PowerFlex 40, 2.2 kW (3.0 HP), 6.0 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D6P0N104	PowerFlex 40, 2.2 kW (3.0 HP), 6.0 A, 380...480 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-D010C104	PowerFlex 40, 4.0 kW (5.0 HP), 10.5 A, 380...480 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-D010F104	PowerFlex 40, 4.0 kW (5.0 HP), 10.5 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D010N104	PowerFlex 40, 4.0 kW (5.0 HP), 10.5 A, 380...480 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-D012F104	PowerFlex 40, 5.5 kW (7.5 HP), 12.0 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D012N104	PowerFlex 40, 5.5 kW (7.5 HP), 12.0 A, 380...480 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote
22B-D017F104	PowerFlex 40, 7.5 kW (10.0 HP), 17.0 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D017N104	PowerFlex 40, 7.5 kW (10.0 HP), 17.0 A, 380...480 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote
22B-D024F104	PowerFlex 40, 11.0 kW (15.0 HP), 24.0 A, 380...480 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-D024N104	PowerFlex 40, 11.0 kW (15.0 HP), 24.0 A, 380...480 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote

460...600 V AC, 3-phase input

ORDER NUMBER	DESCRIPTION	
22B-E1P7C104	PowerFlex 40, 0.75 kW (1.0 HP), 1.7 A, 460...600 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-E1P7F104	PowerFlex 40, 0.75 kW (1.0 HP), 1.7 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E1P7N104	PowerFlex 40, 0.75 kW (1.0 HP), 1.7 A, 460...600 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-E3P0C104	PowerFlex 40, 1.5 kW (2.0 HP), 3.0 A, 460...600 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-E3P0F104	PowerFlex 40, 1.5 kW (2.0 HP), 3.0 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E3P0N104	PowerFlex 40, 1.5 kW (2.0 HP), 3.0 A, 460...600 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote

ORDER NUMBER	DESCRIPTION	
22B-E4P2C104	PowerFlex 40, 2.2 kW (3.0 HP), 4.2 A, 460...600 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-E4P2F104	PowerFlex 40, 2.2 kW (3.0 HP), 4.2 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E4P2N104	PowerFlex 40, 2.2 kW (3.0 HP), 4.2 A, 460...600 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-E6P6C104	PowerFlex 40, 4.0 kW (5.0 HP), 6.6 A, 460...600 V AC 3-phase input, IP66 NEMA 4X/12	Request a Quote
22B-E6P6F104	PowerFlex 40, 4.0 kW (5.0 HP), 6.6 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E6P6N104	PowerFlex 40, 4.0 kW (5.0 HP), 6.6 A, 460...600 V AC 3-phase input, IP20 panel mount, frame B	Request a Quote
22B-E9P9F104	PowerFlex 40, 5.5 kW (7.5 HP), 9.9 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E9P9N104	PowerFlex 40, 5.5 kW (7.5 HP), 9.9 A, 460...600 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote
22B-E012F104	PowerFlex 40, 7.5 kW (10.0 HP), 12.0 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E012N104	PowerFlex 40, 7.5 kW (10.0 HP), 12.0 A, 460...600 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote
22B-E019F104	PowerFlex 40, 11.0 kW (15.0 HP), 19.0 A, 460...600 V AC 3-phase input, IP20 flange mount	Request a Quote
22B-E019N104	PowerFlex 40, 11.0 kW (15.0 HP), 19.0 A, 460...600 V AC 3-phase input, IP20 panel mount, frame C	Request a Quote

Communication adapters, HIMs and covers

ORDER NUMBER	DESCRIPTION	
22-COMM-B	BACnet communication adapter for PowerFlex 40 drives	Request a Quote
22-COMM-C	ControlNet communication adapter for PowerFlex 40 drives	Request a Quote
22-COMM-D	DeviceNet communication adapter for PowerFlex 40 drives	Request a Quote
22-COMM-E	EtherNet/IP communication adapter for PowerFlex 40 drives	Request a Quote
22-COMM-L	LonWorks communication adapter for PowerFlex 40 drives	Request a Quote
22-COMM-P	PROFIBUS DP communication adapter for PowerFlex 40 drives	Request a Quote
22-HIM-A3	Remote handheld LCD HIM, full numeric keypad, IP30 (NEMA Type 1), with 1.0 m cable	Request a Quote
22-HIM-B1	Bezel kit for panel mounting the handheld HIM, IP30 (NEMA Type 1)	Request a Quote
22-HIM-C2S	Remote LCD HIM, panel mount, IP66 (NEMA Type 4X/12), with 2.0 m cable	Request a Quote
22-XCOMM-DC-BASE	External DSI communications kit for 22-COMM adapters, up to 5 drives	Request a Quote
22B-CCB	Communication adapter cover, PowerFlex 40 frame B, adds 25 mm depth	Request a Quote

ORDER NUMBER	DESCRIPTION
22B-CCC	Communication adapter cover, PowerFlex 40 frame C, adds 25 mm depth Request a Quote

Prepared by GEARWELL, 2026-10-14. Allen-Bradley, PowerFlex, StepLogic and Rockwell Automation are trademarks of Rockwell Automation, Inc. GEARWELL is an independent supplier and is not affiliated with or authorized by Rockwell Automation. Catalog numbers and specifications are taken from PowerFlex 4 and 40 AC Drives Technical Data, Rockwell Automation publication 22-TD001J-EN-P (September 2024), pages 8...20. They are given for identification; confirm the full catalog number with the product label before ordering. Official documentation: literature.rockwellautomation.com.