

Beckhoff EtherCAT couplers, EtherCAT Box, Embedded and Industrial PCs, drive technology and accessories, article list

44 Beckhoff articles that GEARWELL lists. Each line gives the Beckhoff product description, protection rating and operating temperature taken from the Beckhoff product page for that article. Ask us for availability, lead time and price for any article below.

EtherCAT couplers and junctions (EK)

ORDER NUMBER	DESCRIPTION	
BK1120	EtherCAT Bus Coupler for standard Bus Terminals; IP20; -25...+60 °C	Request a Quote
BK1150	EtherCAT Compact Bus Coupler; IP20; -25...+60 °C	Request a Quote
BK1250	Compact coupler between EtherCAT Terminals and Bus Terminals; IP20; -25...+60 °C	Request a Quote
EK1100	EtherCAT Coupler; IP20; -25...+60 °C	Request a Quote
EK1110	EtherCAT extension; IP20; -25...+60 °C	Request a Quote
EK1521	1-port EtherCAT fiber-optic junction; IP20; -25...+60 °C	Request a Quote
EK1541	EtherCAT Coupler with ID switch, plastic optical fiber; IP20; -25...+60 °C	Request a Quote
EK1561	1-port EtherCAT plastic optical fiber junction; IP20; -25...+60 °C	Request a Quote
EK1814	EtherCAT Coupler with integrated digital inputs/outputs; IP20; -25...+60 °C	Request a Quote
EK1818	EtherCAT Coupler with integrated digital inputs/outputs; IP20; -25...+60 °C	Request a Quote
EK1828	EtherCAT Coupler with integrated digital inputs/outputs; IP20; -25...+60 °C	Request a Quote
EK1828-0010	EtherCAT Coupler with integrated digital outputs; IP20; -25...+60 °C	Request a Quote
EK1914	EtherCAT Coupler with integrated digital standard and safety I/Os; IP20	Request a Quote
EK9000	ModbusTCP/UDP Bus Coupler; IP20; -25...+60 °C	Request a Quote
EK9500	EtherNet/IP™ Bus Coupler; IP20; -25...+60 °C	Request a Quote

EtherCAT Box modules (EP)

ORDER NUMBER	DESCRIPTION	
EP1008-0001	EtherCAT Box, 8-channel digital input, 24 V DC, 3 ms, M8; IP65; -25...+60 °C	Request a Quote
EP1122-0001	EtherCAT Box, 2-port junction, M8; IP65; -25...+60 °C	Request a Quote
EP2008-0001	EtherCAT Box, 8-channel digital output, 24 V DC, 0.5 A, M8; IP65; -25...+60 °C	Request a Quote
EP2338-0001	EtherCAT Box, 8-channel digital combi, 24 V DC, 10 µs, 0.5 A, M8; IP65; -25...+60 °C	Request a Quote
EP2338-0002	EtherCAT Box, 8-channel digital combi, 24 V DC, 10 µs, 0.5 A, M12; IP65; -25...+60 °C	Request a Quote

ORDER NUMBER	DESCRIPTION	
EP6002-0002	EtherCAT Box, 2-channel communication interface, serial, RS232/RS422/RS485, M12; IP65; -25...+60 °C	Request a Quote
EP6224-2022	EtherCAT Box, 4-channel communication interface, IO-Link, master, Class A, M12; IP65; -25...+60 °C	Request a Quote

EtherCAT Terminals, compact drive technology (EL7xxx)

ORDER NUMBER	DESCRIPTION	
EL7041	EtherCAT Terminal, 1-channel motion interface, stepper motor, 48 V DC, 5 A, with incremental encoder; IP20; 0...55 °C	Request a Quote
EL7211	EtherCAT Terminal, 1-channel motion interface, servomotor, 48 V DC, 4.5 A, resolver; IP20; 0...55 °C	Request a Quote
EL7411	EtherCAT Terminal, 1-channel motion interface, BLDC motor, 48 V DC, 4.5 A, with incremental encoder; IP20; 0...55 °C	Request a Quote

Embedded PCs, Industrial PCs and accessories (CX, C6xxx, CU)

ORDER NUMBER	DESCRIPTION	
C6515-0060	Fanless built-in Industrial PC; outside IP65, inside IP20; outside 0...45 °C, inside 0...55 °C	Request a Quote
C6640-0050	Control cabinet Industrial PC; IP20; 0...55 °C	Request a Quote
C9900-U330	Battery pack; 0...50 °C	Request a Quote
C9900-U332-0010	Battery pack; 0...50 °C	Request a Quote
CU8880-0010	Ethernet controller with USB input; IP20; 0...55 °C	Request a Quote
CX1100-0014	Power supply units and I/O interfaces for CX1030 (service phase); IP20; 0...55 °C	Request a Quote
CX5020	Embedded PC with Intel Atom® (service phase); IP20; -25...+60 °C	Request a Quote
CX5230	Embedded PC with Intel Atom® x5-E3930; IP20; -25...+60 °C	Request a Quote
CX8080	Embedded PC with Arm9™ and RS232/RS485; IP20; 0...55 °C	Request a Quote
CX9020-0111	Embedded PC with Arm® Cortex®-A8; IP20; -25...+60 °C	Request a Quote

Servo drives, servomotors and accessories (AX, AM)

ORDER NUMBER	DESCRIPTION	
AM8051-0G00-9000	Servomotor 6.30 Nm (M0), F5 (104 mm)	Request a Quote
AX5805	TwinSAFE drive option card; 0...50 °C	Request a Quote
AX5911-0000	AX-Bridge quick connection system (distribution), for AX5x01 up to AX5112	Request a Quote
AX8206-0100-0000	Dual-axis module; IP20; 0...40 °C, up to 55 °C with power reduction (see documentation)	Request a Quote

Infrastructure, power supply, connectors and cables

ORDER NUMBER	DESCRIPTION	
CU2208	Infrastructure, 8-port switch, Ethernet, 1 Gbit/s, 24 V DC, RJ45; IP20; 0...55 °C	Request a Quote
CU2508	Infrastructure, 8-port port multiplier, Ethernet, 24 V DC, RJ45; IP20; -25...+55 °C	Request a Quote
PS3031-2420-0001	Power supply PS3000; output: 24 V DC, 20 A; input: 3 AC 380...480 V, 3-phase; IP20; -25...+70 °C	Request a Quote
ZS1000-0620	Socket field assembly for PROFIBUS, Modbus, RS485, shielded	Request a Quote
ZS7000-0002	Plug, field assembly, shielded	Request a Quote

Prepared by GEARWELL, 2026-10-14. Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT P® and TwinSAFE® are registered trademarks of Beckhoff Automation GmbH. GEARWELL is an independent supplier and is not affiliated with or authorized by Beckhoff Automation. Order numbers, descriptions and technical data are taken from the Beckhoff product pages at www.beckhoff.com (English, retrieved 2026-10-14). They are given for identification; confirm the full order number, including any ordering option, before ordering. Official documentation: www.beckhoff.com.