

Beckhoff EtherCAT Terminals, digital input and output, article list

43 Beckhoff articles that GEARWELL lists. Each line gives the Beckhoff product description, protection rating and operating temperature taken from the Beckhoff product page for that article. Ask us for availability, lead time and price for any article below.

EtherCAT Terminals, digital input (EL1xxx)

ORDER NUMBER	DESCRIPTION	
EL1002	EtherCAT Terminal, 2-channel digital input, 24 V DC, 3 ms; IP20; -25...+60 °C	Request a Quote
EL1008	EtherCAT Terminal, 8-channel digital input, 24 V DC, 3 ms; IP20; -25...+60 °C	Request a Quote
EL1024	EtherCAT Terminal, 4-channel digital input, 24 V DC, 3 ms, type 2; IP20; 0...55 °C	Request a Quote
EL1034	EtherCAT Terminal, 4-channel digital input, 24 V DC, 10 µs, potential-free; IP20; -25...+60 °C	Request a Quote
EL1084	EtherCAT Terminal, 4-channel digital input, 24 V DC, 3 ms, ground switching; IP20; 0...55 °C	Request a Quote
EL1088	EtherCAT Terminal, 8-channel digital input, 24 V DC, 3 ms, ground switching; IP20; 0...55 °C	Request a Quote
EL1094	EtherCAT Terminal, 4-channel digital input, 24 V DC, 10 µs, ground switching; IP20; 0...55 °C	Request a Quote
EL1104	EtherCAT Terminal, 4-channel digital input, 24 V DC, 3 ms, 2-/3-wire connection; IP20; -25...+60 °C	Request a Quote
EL1144	EtherCAT Terminal, 4-channel digital input, 12 V DC, 10 µs; IP20; 0...55 °C	Request a Quote
EL1202	EtherCAT Terminal, 2-channel digital input, 24 V DC, 1 µs; IP20; -25...+60 °C	Request a Quote
EL1252	EtherCAT Terminal, 2-channel digital input, 24 V DC, 1 µs, timestamp; IP20; -25...+60 °C	Request a Quote
EL1259	EtherCAT Terminal, 8-channel digital input + 8-channel digital output, 24 V DC, 1 µs, 0.5 A, multi-timestamp; IP20; 0...55 °C	Request a Quote
EL1262	EtherCAT Terminal, 2-channel digital input, 24 V DC, 1 µs, oversampling; IP20; 0...55 °C	Request a Quote
EL1502	EtherCAT Terminal, 2-channel digital input, counter, 24 V DC, 100 kHz; IP20; -25...+60 °C	Request a Quote
EL1808	EtherCAT Terminal, 8-channel digital input, 24 V DC, 3 ms, 2-wire connection; IP20; -25...+60 °C	Request a Quote
EL1809	EtherCAT Terminal, 16-channel digital input, 24 V DC, 3 ms; IP20; -25...+60 °C	Request a Quote

ORDER NUMBER	DESCRIPTION	
EL1819	EtherCAT Terminal, 16-channel digital input, 24 V DC, 10 µs; IP20; -25...+60 °C	Request a Quote
EL1859	EtherCAT Terminal, 8-channel digital input + 8-channel digital output, 24 V DC, 3 ms, 0.5 A; IP20; -25...+55 °C	Request a Quote
EL1889	EtherCAT Terminal, 16-channel digital input, 24 V DC, 3 ms, ground switching; IP20; -25...+60 °C	Request a Quote
EL1904	EtherCAT Terminal, 4-channel digital input, 24 V DC, TwinSAFE; IP20	Request a Quote

EtherCAT Terminals, digital output (EL2xxx)

ORDER NUMBER	DESCRIPTION	
EL2002	EtherCAT Terminal, 2-channel digital output, 24 V DC, 0.5 A; IP20; -25...+60 °C	Request a Quote
EL2004	EtherCAT Terminal, 4-channel digital output, 24 V DC, 0.5 A; IP20; -25...+60 °C	Request a Quote
EL2008	EtherCAT Terminal, 8-channel digital output, 24 V DC, 0.5 A; IP20; -25...+60 °C	Request a Quote
EL2022	EtherCAT Terminal, 2-channel digital output, 24 V DC, 2 A; IP20; -25...+60 °C	Request a Quote
EL2024	EtherCAT Terminal, 4-channel digital output, 24 V DC, 2 A; IP20; -25...+60 °C	Request a Quote
EL2034	EtherCAT Terminal, 4-channel digital output, 24 V DC, 2 A, with diagnostics; IP20; -25...+60 °C	Request a Quote
EL2042	EtherCAT Terminal, 2-channel digital output, 24 V DC, 2 x 4 A/1 x 8 A; IP20; -25...+60 °C	Request a Quote
EL2084	EtherCAT Terminal, 4-channel digital output, 24 V DC, 0.5 A, ground switching; IP20; 0...55 °C	Request a Quote
EL2124	EtherCAT Terminal, 4-channel digital output, 5 V DC, 20 mA; IP20; 0...55 °C	Request a Quote
EL2202	EtherCAT Terminal, 2-channel digital output, 24 V DC, 0.5 A, push-pull, tri-state; IP20; -25...+55 °C	Request a Quote
EL2212	EtherCAT Terminal, 2-channel digital output, 24...72 V DC, 10 A, overexcitation, multi-timestamp; IP20; -25...+55 °C	Request a Quote
EL2252	EtherCAT Terminal, 2-channel digital output, 24 V DC, 0.5 A, timestamp; IP20; 0...55 °C	Request a Quote
EL2262	EtherCAT Terminal, 2-channel digital output, 24 V DC, 0.5 A, oversampling; IP20; 0...55 °C	Request a Quote
EL2502	EtherCAT Terminal, 2-channel PWM output, 24 V DC, 0.5 A; IP20; -25...+55 °C	Request a Quote
EL2522	EtherCAT Terminal, 2-channel pulse train output, incr. enc. simulation, RS422, 50 mA; IP20; -25...+60 °C	Request a Quote
EL2535	EtherCAT Terminal, 2-channel PWM output, 24 V DC, 1 A, current-controlled; IP20; 0...55 °C	Request a Quote

ORDER NUMBER	DESCRIPTION	
EL2595	EtherCAT Terminal, 1-channel LED output, 2...48 V DC, 0.7 A; IP20; 0...55 °C	Request a Quote
EL2612	EtherCAT Terminal, 2-channel relay output, 125 V AC, 30 V DC, 0.5 A AC, 2 A DC; IP20; -25...+55 °C	Request a Quote
EL2622	EtherCAT Terminal, 2-channel relay output, 230 V AC, 30 V DC, 5 A, without power contacts; IP20; -25...+55 °C	Request a Quote
EL2798	EtherCAT Terminal, 8-channel solid-state relay output, 30 V AC, 48 V DC, 2 A, potential-free; IP20; 0...55 °C	Request a Quote
EL2808	EtherCAT Terminal, 8-channel digital output, 24 V DC, 0.5 A, 2-wire connection; IP20; -25...+60 °C	Request a Quote
EL2819	EtherCAT Terminal, 16-channel digital output, 24 V DC, 0.5 A, with extended diagnostics; IP20; -25...+55 °C	Request a Quote
EL2872	EtherCAT Terminal, 16-channel digital output, 24 V DC, 0.5 A, flat-ribbon cable; IP20; -25...+55 °C	Request a Quote

Prepared by GEARWELL, 2026-10-14. Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT P® and TwinSAFE® are registered trademarks of Beckhoff Automation GmbH. GEARWELL is an independent supplier and is not affiliated with or authorized by Beckhoff Automation. Order numbers, descriptions and technical data are taken from the Beckhoff product pages at www.beckhoff.com (English, retrieved 2026-10-14). They are given for identification; confirm the full order number, including any ordering option, before ordering. Official documentation: www.beckhoff.com.