

EUCHNER safety switches, actuators and accessories

35 catalog numbers for EUCHNER TP, STP, NP, GP and NZ safety switches, CES and CET transponder-coded safety switches, MGB gate boxes, actuators, safety bolts, a light curtain and a connection cable. Ask us for availability, lead time and price for any item below.

TP, STP and TP-BI safety switches with guard locking

ORDER NUMBER	DESCRIPTION	
STP3A-2131A024M	Safety switch STP with guard locking, power to unlock, solenoid 24 V AC/DC, switching element 2131, 3 x M20 x 1.5, order no. 091493	Request a Quote
TP1-4131A024M	Safety switch TP with guard locking, power to unlock, solenoid 24 V AC/DC, switching element 4131 (2 positively driven + 2 NO), order no. 084115	Request a Quote
TP3-2131A024M	Safety switch TP with guard locking, closed-circuit current principle, solenoid 24 V AC/DC, switching element 2131, 3 x M20 x 1.5, order no. 084142	Request a Quote
TP3-4131K024M	Safety switch TP with guard locking, power to unlock, solenoid 24 V AC/DC, switching element 4131, increased vertical overtravel, order no. 084256	Request a Quote
TP3-4141A024M	Safety switch TP with guard locking, closed-circuit current principle, solenoid 24 V AC/DC, switching element 4141, 3 x M20 x 1.5, order no. 084270	Request a Quote
TP3-4141A024MC1844	Safety switch TP with guard locking, power to unlock, solenoid 24 V AC/DC, switching element 4141, lockable auxiliary release, order no. 096893	Request a Quote
TP3-4141A024MC2184	Safety switch TP3 with guard locking, power to unlock, solenoid 24 V AC/DC, switching element 4141, version C2184, order no. 100139	Request a Quote
TP4-4131A024M	Safety switch TP with guard locking, open-circuit current principle, solenoid 24 V AC/DC, switching element 4131, 3 x M20 x 1.5, order no. 084132	Request a Quote
TP4-4141A024M	Safety switch TP with guard locking, open-circuit current principle, solenoid 24 V AC/DC, switching element 4141, 3 x M20 x 1.5, order no. 084275	Request a Quote
TP4-4141A024MC2074	Safety switch TP4-4141 variant with guard locking, 4NC contact element, actuator head adjustable, 3 x M20x1,5 thread, order no. 094844	Request a Quote

NP, GP, NZ, NM and RGBF safety and position switches, actuators

ORDER NUMBER	DESCRIPTION	
BETAETIGER-P-G	Straight actuator BETAETIGER-P-G for NP/GP/TP safety switches, stainless steel, two safety screws, order no. 059226	Request a Quote
BETAETIGER-P-W	Bent actuator BETAETIGER-P-W for NP/GP/TP safety switches, stainless steel, two safety screws, order no. 059227	Request a Quote

ORDER NUMBER	DESCRIPTION	
BETAETIGER-S-GT-SN	Straight actuator S with rubber bush for SGA/SGP/STA/STP/STM safety switches, stainless steel, order no. 095738	Request a Quote
BETAETIGER-Z-G	Straight actuator BETAETIGER-Z-G for NZ.VZ, NZ.VZ.VS and TZ safety switches, overtravel 4 mm, order no. 016849	Request a Quote
GP1-2131A-M	Safety switch GP, separate actuator, switching element 2131 (3 positively driven + 1 NO), 3 x M20 x 1.5, order no. 090255	Request a Quote
NM01VZA-M	Safety switch NM.VZ, short housing, separate actuator, switching element ES01 (1 positively driven contact), M16 x 1.5, order no. 084451	Request a Quote
NP1-628AS-M	Safety switch NP without guard locking, switching element 628 (1 NC + 1 NO), cable entry M20 x 1.5, order no. 083688	Request a Quote
NP1-638AS-M	Safety switch NP without guard locking, switching element 638 (2 NC), cable entry M20 x 1.5, order no. 083691	Request a Quote
NZ2RS-511SVM5	Safety switch NZ.RS with roller plunger, steel roller 12 mm, switching element 511 (1 positively driven + 1 NO), M12 5-pin, order no. 090027	Request a Quote
RGBF02D12-502-M	Precision multiple limit switch RGBF, 12 mm plunger spacing, 2 switching elements ES 502 E (snap-action 1 NC + 1 NO), order no. 082312	Request a Quote

CES and CET transponder-coded non-contact safety switches and evaluation units

ORDER NUMBER	DESCRIPTION	
CES-A-BBA-071840	Actuator CES-A-BBA, cube shape 42 x 25 mm, PPS plastic, IP65/IP67/IP69/IP69K, order no. 071840	Request a Quote
CES-A-C5H-01	Non-contact safety switch CES-A, transponder-coded, unicode, 2 semiconductor safety outputs, M12 8-pin, order no. 091458	Request a Quote
CES-A-W5H-01	Non-contact safety switch CES-A, transponder-coded, multicode, 2 semiconductor safety outputs, M12 8-pin, order no. 097525	Request a Quote
CES-AP-C01-CH-SA-100250	Transponder-coded safety switch CES-AP-C01, multicode, 2 safety outputs, DIA output, M12 8-pin, 24 V DC, order no. 100250	Request a Quote
CET-A-BWK-50X	Actuator CET-A-BWK-50X for CET read heads and safety switches, transponder coded, stainless steel, IP67, order no. 096327	Request a Quote
CET3-AR-CRA-CH-50X-SG-110906	Transponder-coded safety switch CET-AR with guard locking, closed-circuit current principle, multicode, 2 x M12 (5- and 8-pin), order no. 110906	Request a Quote
CTP-L1-AP-U-HA-AZ-SA-124225	Transponder-coded safety switch CTP-AP with guard locking, closed-circuit current principle, unicode, M12 8-pin, order no. 124225	Request a Quote

MGB multifunctional gate boxes and BTC safety bolts

ORDER NUMBER	DESCRIPTION	
BTC-T/GP-S-TH-01-F	Bolt BTC with escape release for one TP...A or GP safety switch, aluminum, detent in open position, order no. 106302	Request a Quote
MGB-L1H-APA-R-121369	MGB locking set MGB-L1H-APA, guard locking by spring force, emergency stop and 3 illuminated pushbuttons, RC18, unicode, order no. 121369	Request a Quote
MGB-L1HB-PNA-R-121832	MGB guard locking set with Profinet/PROFIsafe bus module MGB-L1B-PNA, power to unlock, push-pull connectors, door hinge right, order no. 121832	Request a Quote
MGB-L2H-ARA-R-105786	MGB guard locking set: handle module + locking module MGB-L2-ARA, power to lock, AR series wiring, door hinge right, order no. 105786	Request a Quote
RIEDEL TP-A	Bolt RIEDEL TP-A for GP and TP safety switches, approach direction A, doors hinged on the right, door gap approx. 15 mm, order no. 084430	Request a Quote
RIEDEL TP-C	Bolt RIEDEL TP-C for GP and TP safety switches, approach direction C, doors hinged on the left, door gap approx. 15 mm, order no. 084432	Request a Quote

Other EUCHNER safety devices: enabling and hand-held units, light curtains, cables and connectors

ORDER NUMBER	DESCRIPTION	
C-M12F05-05X034PU05, 0-M12M05-119932	Connecting cable M12 female plug to M12 male plug, 5-pin, straight, PUR, 5 x 0.34 mm ² , 5 m, order no. 119932	Request a Quote
LCA-2TR-40-910-AP-156652	Safety light curtain LCA-2TR-40-910, type 2, resolution 40 mm, protective field height 910 mm, range 12 m, M12, order no. 156652	Request a Quote

Prepared by GEARWELL, 2026-10-14. EUCHNER is a trademark of EUCHNER GmbH + Co. KG. GEARWELL is an independent supplier and is not affiliated with or authorized by EUCHNER GmbH + Co. KG. Catalog numbers, ratings and specifications are taken from EUCHNER data sheet "TP4-4141A024MC2074", doc. no. 2094894, version 4, 26.01.15; EUCHNER operating instructions "Safety Switch NP...", doc. no. 2083684, version 13-07/25; EUCHNER data sheet "MGB-L..B-PNA...", doc. no. 2122062, version 3, 25.09.17; EUCHNER operating instructions "Safety Switch TP...", doc. no. 2084123, version 21-03/25; EUCHNER data sheet "Anbauanleitung / Mounting instruction" (bolt BTC-T/GP), doc. no. 2127430, version 2, 21.11.17; EUCHNER product pages for the listed order numbers (www.euchner.com/en-us/a/<order no.>), retrieved 2026-10-15). They are given for identification; confirm the full catalog number with the product label before ordering. Official documentation: www.euchner.com.