

ifm AS-Interface modules, gateways and accessories, article list

29 ifm AS-Interface (AS-i) articles that GEARWELL lists: I/O modules for the field and the control cabinet, gateways, IO-Link masters with AS-i interface and AS-i accessories. Each line gives the ifm type designation and key technical data: inputs and outputs, AS-i version and slave profile, operating voltage, dimensions, mounting, connection and protection rating, taken from the technical data on the ifm product page for that article. Ask us for availability, lead time and price for any article below.

AS-i I/O modules

ORDER NUMBER	DESCRIPTION	
AC009S	SmartLine SafetyModul; 2 digital safety inputs, 2 relay outputs; AS-i 2.11 / 3.0; profile S-7.B.E; 26.5...31.6 V DC; 93 x 25.4 x 108 mm; DIN rail TH35; IP20	Request a Quote
AC2024	AirBox 2DI 2PO M12; 2 digital inputs, 2 pneumatic outputs; profile S-3.F.F; 26.5...31.6 V DC; 103 x 45 x 46 mm; on FC or SC lower part; M12 (A-coded, 4-pin); IP65	Request a Quote
AC2032	EMS/Module/4DI/CCT; 4 digital inputs; profile S-0.0.F; 26.5...31.6 V DC; 102 x 45 x 50 mm; on FC or SC lower part; IP65	Request a Quote
AC2035	EEMS/Module/4DI/4DO/T/CCT; 4 digital inputs, 4 digital outputs; profile S-7.F.F; 26.5...31.6 V DC; 102 x 91 x 71 mm; on FC-E or SC lower part; IP65	Request a Quote
AC2046	AirBox 2DI 1PO M12; 2 digital inputs, 1 pneumatic output; profile S-3.F; 26.5...31.6 V DC; 85 x 45 x 52 mm; screw mounting; M12; IP65	Request a Quote
AC2257	SmartL25 4DI 4DO T C; 4 digital inputs, 4 digital outputs; AS-i 2.11 / 3.0; profile S-7.0.E; 26.5...31.6 V DC, AUX 20...30 V DC; 93 x 25.4 x 108 mm; DIN rail TH35; IP20	Request a Quote
AC2261	SmartLine25 4DI 4DO A/B T C; 4 digital inputs, 4 digital outputs; AS-i 3.0; profile S-7.A.7; A/B addressing; 26.5...31.6 V DC, AUX 20...30 V DC; 93 x 25.4 x 108 mm; DIN rail TH35; IP20	Request a Quote
AC2267	SmartLine25 4DI 4DO T C AUX; 4 digital inputs, 4 digital outputs; AS-i 3.0; profile S-7.A.7; A/B addressing; 26.5...31.6 V DC, AUX 20 V DC; 93 x 25.4 x 108 mm; DIN rail TH35; IP20	Request a Quote
AC2412	CompactModule 4DI 4DO T M12; 4 digital inputs, 4 digital outputs; AS-i 2.11 / 3.0; profile S-7.0.E; 26.5...31.6 V DC, AUX 10...30 V DC; 152 x 60 x 27 mm; flat cable, backplane mounting; M12 (A-coded, 5-pin); IP67	Request a Quote
AC2459	CompactLM12 4DI-Y 4DO T; 4 digital inputs, 4 digital outputs; AS-i 2.11 / 3.0; profile S-7.F.E; 26.5...31.6 V DC, AUX 10...30 V DC; 152 x 60 x 27 mm; flat cable, backplane mounting; 4 x M12 (A-coded, 3-pin); IP67	Request a Quote
AC2516	ClassicLine90 4AI (C) M12 IP67; 4 4...20 mA analog inputs; profile S-7.3.E; 26.5...31.6 V DC, AUX 24...30 V DC; 83 x 90 x 44 mm; on FC or FC-E lower part; M12 (A-coded, 4-pin); IP67	Request a Quote
AC2519	ClassicLine90 4AO (V) M12 IP67; 4 0...10 V analog outputs; profile S-7.3.6; 26.5...31.6 V DC, AUX 24...30 V DC; 83 x 90 x 44 mm; on FC or FC-E lower part; M12 (A-coded, 3-pin); IP67	Request a Quote

ORDER NUMBER	DESCRIPTION	
AC2619	UniversalModule 2AO(V) IP65; 2 0...10 V analog outputs; profile S-7.3.5; 26.5...31.6 V DC, AUX 24...30 V DC; 102 x 91 x 71 mm; on FC-E lower part; IP65	Request a Quote
AC2910	ProcessLine 8DI IP69K; 8 digital inputs; AS-i 2.1; profile S-0.A.E; A/B addressing; 26.5...31.6 V DC; Ø 137.3 x 80 mm; mounting base; M12 (A-coded, 5-pin); IP68, IP69K	Request a Quote
AC3200	SmartL25 4DI 4DO T C; 4 digital inputs, 4 digital outputs; AS-i 3.0; profile S-7.A.7; A/B addressing; 18...31.6 V DC, AUX 20...30 V DC; 129.3 x 25.4 x 59.3 mm; DIN rail TH35; IP20	Request a Quote
AC505A	ClassicLine 4DI II 3D; 4 digital inputs; AS-i 2.11 / 3.0; profile S-0.0.E; 26.5...31.6 V DC; 103 x 45 x 44.7 mm; flat cable, DIN rail TH35; 4 x M12 (A-coded, 4-pin); IP50	Request a Quote
AC509S	ClassicLine 2x2SI 2DOT 2LO; 4 digital safety inputs, 2 digital outputs; AS-i 2.11 / 3.0; profile S-7.B.E; 26.5...31.6 V DC; 103 x 45 x 44.7 mm; flat cable, DIN rail TH35; 2 x M12 (A-coded, 4-pin); IP67	Request a Quote
AC5205	ClassicLine 4DI IP67; 4 digital inputs; AS-i 2.11 / 3.0; profile S-0.0.E; 26.5...31.6 V DC; 103 x 45 x 44.7 mm; flat cable, DIN rail TH35; M12 (A-coded, 4-pin); IP67	Request a Quote
AC5211	ClassicLine 2DI 2DO-Y IP67; 2 digital inputs, 2 digital outputs; AS-i 2.11 / 3.0; profile S-3.0.E; 26.5...31.6 V DC, AUX 15...30 V DC; 103 x 45 x 44.7 mm; flat cable, DIN rail TH35; M12 (A-coded, 5-pin); IP67	Request a Quote
AC5215	ClassicLine 4DI-Y IP67; 4 digital inputs; AS-i 2.11 / 3.0; profile S-0.A.E; A/B addressing; 26.5...31.6 V DC; 103 x 45 x 44.7 mm; flat cable, DIN rail TH35; M12; IP67	Request a Quote
AC5235	ClassicLine 4DI-Y 4DO-Y IP67; 4 digital inputs, 4 digital outputs; AS-i 3.0; profile S-7.A.7; A/B addressing; 26.5...31.6 V DC, AUX 15...30 V DC; 103 x 90 x 44.2 mm; quick mounting on flat cable, DIN rail TH35; M12; IP67	Request a Quote
AC5291	ClassicLine 4DI-Y IP67; 4 digital inputs; AS-i 2.11 / 3.0; profile S-0.A.E; A/B addressing; 26.5...31.6 V DC; 103 x 45 x 44.7 mm; quick mounting on flat cable, DIN rail TH35; M12; IP67	Request a Quote

AS-i gateways and IO-Link masters with AS-i interface

ORDER NUMBER	DESCRIPTION	
AC1422	AS-i Gateway 2Master EIP; 2 AS-i masters; EtherNet/IP (RJ45); AS-i 3.0; 18...32 V DC AUX, AS-i 21...31.6 V DC; 135.5 x 93 x 106.2 mm; DIN rail TH35; IP20	Request a Quote
AC1433	SmartPLC DataLine 1ASi ECAT; 1 AS-i master; EtherCAT (RJ45); AS-i 3.0; 18...32 V DC AUX, AS-i 21...31.6 V DC; 135.5 x 93 x 106.2 mm; DIN rail TH35; IP20	Request a Quote
AC6001	IO-Link Master AS-i 4P IP69K; 4 IO-Link ports class A; 8 digital inputs, 4 digital outputs; AS-i 2.11 / 3.0; profile S-7.3.E (CTT1 slave); 18...31.6 V DC, AUX 20...30 V DC; 124 x 59.3 x 38.4 mm; backplane mounting; 4 x M12 (A-coded, 4-pin); IP65, IP66, IP67, IP69K	Request a Quote

ORDER NUMBER	DESCRIPTION	
AC6003	IO-Link Master AS-i 2P IP69K; 2 IO-Link ports class A; 4 digital inputs, 2 digital outputs; AS-i 2.11 / 3.0; profile S-7.3.E (CTT1 slave); 26...31.6 V DC; 124 x 59.3 x 38.4 mm; backplane mounting; 2 x M12 (A-coded, 4-pin); IP65, IP66, IP67, IP69K	Request a Quote

AS-i accessories

ORDER NUMBER	DESCRIPTION	
AC1154	Addressing unit AS-i 3.0; AS-i 3.0; A/B addressing; 209 x 80 x 35 mm; IP20	Request a Quote
AC1250	AS-i Data Decoupler; 21.5...31.6 V DC; 128.2 x 45 x 65.5 mm; IP20	Request a Quote
AC5051	Splitter Box 8SB IP67; 18...31.6 V DC, AUX 15...30 V DC; 208 x 59.3 x 38.4 mm; backplane mounting; M12 (A-coded, 4-pin); IP65, IP66, IP67	Request a Quote

Prepared by GEARWELL, 2026-10-14. ifm is a trademark of ifm electronic gmbh. GEARWELL is an independent supplier and is not affiliated with or authorized by ifm electronic. Article numbers, type designations and technical data are taken from the ifm electronic product pages at www.ifm.com (English, retrieved 2026-10-14). They are given for identification; confirm the article number on the device label before ordering. Official documentation: www.ifm.com.