

Mitsubishi Electric MELSEC modules and GOT terminals

27 catalog numbers for Mitsubishi Electric MELSEC-Q, iQ-R and L series CPUs, I/O, analog, counter, loop control and MODBUS modules, CC-Link remote I/O, an alpha2 GSM cable and GOT2000, GOT SIMPLE and GOT1000 operator terminals. Ask us for availability, lead time and price for any item below.

MELSEC iQ-R, Q and L series PLC CPUs, I/O and special function modules

ORDER NUMBER	DESCRIPTION	
L60AD2DA2	MELSEC-L analog I/O module, 2 inputs and 2 outputs, -10 to 10VDC or 0 to 20mADC, 18-point terminal block	Request a Quote
Q04UDEHCPU	MELSEC-Q Universal model QCPU, 40K steps, 9.5ns LD, 4096 I/O points, built-in Ethernet 100/10Mbps	Request a Quote
Q06PHCPU	MELSEC-Q Process CPU, 60K steps, 34ns LD, 4096 I/O points, FBD process control, 0.64A at 5VDC	Request a Quote
Q62HLC	MELSEC-Q loop control module, 2 analog inputs (thermocouple/voltage/current), 2 outputs 4 to 20mA, PID	Request a Quote
Q66AD - DG	MELSEC-Q channel isolated A/D converter with 2-wire transmitter supply, 6 channels, 4 to 20mADC, 40-pin connector	Request a Quote
Q68AD - G	MELSEC-Q channel isolated A/D converter, 8 channels, -10 to 10VDC or 0 to 20mADC, 40-pin connector	Request a Quote
QD62	MELSEC-Q high-speed counter module, 2 channels, 200 kPPS, 5/12/24 V DC inputs, sink coincidence outputs	Request a Quote
QJ71MB91	MELSEC-Q MODBUS serial interface module, RS-232 and RS-422/485 channels, master/slave, up to 115200bps	Request a Quote
QX40 - S1	MELSEC-Q DC input module, 16 points, positive common, 24VDC approx. 6mA, high-speed response setting	Request a Quote
QY71	MELSEC-Q transistor output module, 32 points, sink type, 5/12VDC, 16mA/point, 40-pin connector	Request a Quote
R35B	MELSEC iQ-R main base unit, 5 I/O module slots, 0.58A at 5VDC, 245mm wide	Request a Quote
R60ADV8	MELSEC iQ-R A/D converter module, 8 voltage input channels, -10 to 10VDC, 80µs/CH, 18-point terminal block	Request a Quote

CC-Link remote I/O and network modules

ORDER NUMBER	DESCRIPTION	
AJ65SBTB1 - 16T	CC-Link compact remote I/O module, 16 transistor outputs, sink type, 12/24VDC, 0.5A/point	Request a Quote
AJ65SBTB2N - 16S	CC-Link compact remote I/O module, 16 triac outputs, 100 to 240VAC, 0.6A/point, 34-point terminal block	Request a Quote
NZ2EX2B - 60DA4	CC-Link IE Field extension D/A converter module, 4 analog outputs, -10 to 10VDC or 0 to 20mADC	Request a Quote

GOT2000, GOT SIMPLE and GOT1000 operator terminals

ORDER NUMBER	DESCRIPTION	
GS2107-WTBD	GOT SIMPLE GS21, 7" TFT color, WVGA 800 x 480, RS-232, RS-422, Ethernet, 24 V DC	Request a Quote
GS2107-WTBD-N	GOT SIMPLE GS21, 7" TFT color, WVGA 800 x 480, RS-232, RS-422/485, Ethernet, 24 V DC	Request a Quote
GS2110-WTBD-N	GOT SIMPLE GS21, 10" TFT color, WVGA 800 x 480, RS-232, RS-422/485, Ethernet, 24 V DC	Request a Quote
GT1555-VTBD	GOT1000 GT15, 5.7" TFT color, 640 x 480, 65536 colors, RS-232, USB, CF card slot, 24 V DC	Request a Quote
GT1675-VNBA	GOT1000 GT16, 10.4" TFT color, 640 x 480, 4096 colors, Ethernet, RS-232, RS-422/485, 100-240 V AC	Request a Quote
GT2505-VTBD	GOT2000 GT25, 5.7" TFT color, VGA 640 x 480, analog resistive touch, 24 V DC	Request a Quote
GT27-IF1000	GOT2000 GT27 video signal conversion unit, supplied in the GT27 video, RGB and multimedia unit sets	Request a Quote
GT2708-VTBD	GOT2000 GT27, 8.4" TFT color, VGA 640 x 480, analog resistive touch, 24 V DC	Request a Quote
GT2710-VTBA	GOT2000 GT27, 10.4" TFT color, VGA 640 x 480, analog resistive touch, black bezel, 100-240 V AC	Request a Quote
GT2715-XTBA	GOT2000 GT27, 15" TFT color, XGA 1024 x 768, analog resistive touch, 100-240 V AC	Request a Quote
GT2715-XTBD	GOT2000 GT27, 15" TFT color, XGA 1024 x 768, analog resistive touch, 24 V DC	Request a Quote

Other Mitsubishi Electric products

ORDER NUMBER	DESCRIPTION	
AL2-GSM-CAB	alpha2 series modem cable for normal or GSM modems, 9-pin D-Sub male modem connector	Request a Quote

Prepared by GEARWELL, 2026-10-14. MELSEC, GOT, MELSERVO, FREQROL and CC-Link are trademarks or registered trademarks of Mitsubishi Electric Corporation. GEARWELL is an independent supplier and is not affiliated with or authorized by Mitsubishi Electric Corporation. Catalog numbers, ratings and specifications are taken from Mitsubishi Electric manual "QCPU User's Manual (Hardware Design, Maintenance and Inspection)", SH(NA)-080483ENG-BC; Mitsubishi Electric manual "Channel Isolated Analog-Digital Converter Module/Channel Isolated Analog-Digital Converter Module (With Signal Conditioning Function) User's Manual", SH(NA)-080647ENG-N; Mitsubishi Electric manual "I/O Module Type Building Block User's Manual", SH(NA)-080042-AH; Mitsubishi Electric manual "High-Speed Counter Module User's Manual", SH(NA)-080036-R; Mitsubishi Electric manual "Loop Control Module User's Manual", SH(NA)-080573ENG-H; Mitsubishi Electric manual "MODBUS Interface Module User's Manual", SH(NA)-080578ENG-K; Mitsubishi Electric manual "MELSEC iQ-R Analog-Digital Converter Module User's Manual (Startup)", SH(NA)-081232ENG-E; Mitsubishi Electric manual "MELSEC iQ-R Module Configuration Manual", SH(NA)-081262ENG-AU; Mitsubishi Electric manual "MELSEC-L Analog Input/Output Module User's Manual", SH(NA)-081167ENG-E; Mitsubishi Electric manual "CC-Link System Compact Type Remote I/O Module User's Manual", SH(NA)-4007-AM; Mitsubishi Electric manual "CC-Link IE Field Network Digital-Analog Converter Module User's Manual", SH(NA)-081453ENG-H; Mitsubishi Electric manual "AL2-GSM-CAB Hardware manual", JY992D97201, rev. L; Mitsubishi Electric manual "GOT2000 Series User's Manual (Hardware)", SH(NA)-081194ENG, rev. AW (Apr. 2026); Mitsubishi Electric manual "GOT SIMPLE Series User's Manual", JY997D52901, rev. Y (Apr. 2026); Mitsubishi Electric manual "GT15 User's Manual", SH(NA)-080528ENG, rev. AL (Apr. 2023); Mitsubishi Electric manual "GT16 User's Manual (Hardware)", SH(NA)-080928ENG, rev. W (Apr. 2023). They are given for identification; confirm the full catalog number with the product label before ordering. Official documentation: www.mitsubishielectric.com/fa.