

WAGO I/O System 750 modules

81 catalog numbers for WAGO I/O System 750 fieldbus couplers and controller, digital and analog I/O, function, communication, intrinsically safe, supply and segment modules. Ask us for availability, lead time and price for any item below.

Fieldbus couplers

ORDER NUMBER	DESCRIPTION	
750-303	PROFIBUS DP fieldbus coupler, 1st generation, D-sub 9 socket, 9.6 kBd ... 12 MBd	Request a Quote
750-306	DeviceNet fieldbus coupler, 5-pole male connector, up to 500 kBd	Request a Quote
750-346	DeviceNet fieldbus coupler ECO, 5-pole male connector, up to 500 kBd	Request a Quote
750-347	CANopen fieldbus coupler ECO, MCS 5-pole male connector, 10 kBd ... 1 MBd	Request a Quote
750-842	ETHERNET TCP/IP programmable fieldbus controller, 10 Mbit/s, RJ-45, MODBUS/TCP	Request a Quote

750 XTR series

ORDER NUMBER	DESCRIPTION	
750-601/040-000	XTR power supply module 24 VDC with fuse holder, 6.3 A, -40 ... +70 °C	Request a Quote

Digital input modules

ORDER NUMBER	DESCRIPTION	
750-1405	16-channel digital input, 24 VDC, 3 ms input filter, high-side switching, 1-wire	Request a Quote
750-1415	8-channel digital input, 24 VDC, 3 ms input filter, 2-wire connection	Request a Quote
750-403	4-channel digital input, 24 VDC, 0.2 ms input filter, high-side switching	Request a Quote
750-414	4-channel digital input, 5 VDC, 0.2 ms input filter	Request a Quote
750-430	8-channel digital input, 24 VDC, 3 ms input filter, 1-wire	Request a Quote
750-431	8-channel digital input, 24 VDC, 0.2 ms input filter, 1-wire	Request a Quote

Digital output modules

ORDER NUMBER	DESCRIPTION	
750-1505	16-channel digital output, 24 VDC, 0.5 A, low-side switching, 1-wire	Request a Quote
750-504	4-channel digital output, 24 VDC, 0.5 A, high-side switching	Request a Quote
750-512	2-channel relay output module, 2 make contacts, 250 VAC/30 VDC, 2 A	Request a Quote
750-515	4-channel relay output, 250 VAC, 2 A, potential-free, 4 make contacts	Request a Quote
750-517	2-channel relay output, 250 VAC, potential-free, 2 changeover contacts	Request a Quote

ORDER NUMBER	DESCRIPTION	
750-519	4-channel digital output module DC 5 V, 20 mA, high-side switching	Request a Quote
750-523	1-channel relay output, 16 A, potential-free, 1 make contact, manual operation	Request a Quote
750-527	4-channel solid-state output, 30 VAC/DC, 2.0 A per channel	Request a Quote
750-528	4-channel solid-state output, 30 VAC/DC, 2.0 A per channel, isolated	Request a Quote
750-530	8-channel digital output, 24 VDC, 0.5 A, high-side switching, 1-wire	Request a Quote
750-536	8-channel digital output, 24 VDC, 0.5 A, low-side switching, 1-wire	Request a Quote
750-537	8-channel digital output, 24 VDC, 0.5 A, with diagnostics	Request a Quote
750-542	2-channel relay output, 230 VAC, 2 A, 2 make contacts, non-floating	Request a Quote
750-543	2-channel relay output, 230 VAC, 2 A, potential-free, 2 make contacts	Request a Quote

Analog input modules

ORDER NUMBER	DESCRIPTION	
750-453	4-channel analog input, 0 ... 20 mA, single-ended, 12 bits	Request a Quote
750-459	4-channel analog input, 0 ... 10 VDC, single-ended, 12 bits	Request a Quote
750-461	2-channel analog input for Pt100/RTD resistance sensors, 2-wire or 3-wire	Request a Quote
750-469/000-006	2-channel analog input for thermocouple J, with diagnostics	Request a Quote
750-478	2-channel analog input, 0 ... 10 VDC, single-ended, 16 bits	Request a Quote
750-479	2-channel analog input, ± 10 VDC, differential, 14 bits	Request a Quote

Analog output modules

ORDER NUMBER	DESCRIPTION	
750-550	2-channel analog output, 0 ... 10 VDC, 12 bits	Request a Quote
750-552	2-channel analog output, 0 ... 20 mA, 12 bits	Request a Quote
750-553	4-channel analog output, 0 ... 20 mA, 12 bits	Request a Quote
750-554	2-channel analog output, 4 ... 20 mA, 12 bits	Request a Quote
750-554/000-200	2-channel analog output, 4 ... 20 mA, 12 bits, S5 data format	Request a Quote
750-555	4-channel analog output, 4 ... 20 mA, 12 bits	Request a Quote
750-557	4-channel analog output, ± 10 VDC, 12 bits	Request a Quote
750-597	8-channel analog output, 0 ... 10 VDC/ ± 10 V, 12 bits, 16 connectors	Request a Quote

Function and technology modules

ORDER NUMBER	DESCRIPTION	
750-632	Proportional valve module, 2 bipolar PWM outputs, 2 A / 1.6 A per channel, 2 DI	Request a Quote
750-635	Digital impulse interface for start/stop position sensors, RS-422, 1 μ m resolution	Request a Quote

ORDER NUMBER	DESCRIPTION	
750-636	DC drive controller, 24 VDC motor, 5 A, incremental encoder input, 3 DI	Request a Quote
750-637	Incremental encoder interface, RS-422 inputs, 32 bits, 250 kHz, 4x evaluation	Request a Quote
750-637/000-001	Incremental encoder interface, 24 VDC differential inputs, 32 bits, 250 kHz	Request a Quote
750-638	2 up/down counters, 16 bits, 500 Hz, 24 VDC inputs	Request a Quote
750-640	RTC module, real-time clock with DCF77 antenna input and 32-channel time switch	Request a Quote
750-645	2-channel vibration velocity and bearing condition monitoring module, 2 DO	Request a Quote
750-670	Stepper controller, RS-422/24 VDC pulse/direction outputs, 20 mA, 2 DI	Request a Quote
750-671	Stepper controller with power driver for 2-phase stepper motors, 24 VDC, 1.5 A	Request a Quote

Communication modules

ORDER NUMBER	DESCRIPTION	
750-641	DALI/DSI master module, up to 64 DALI or 100 DSI slaves, 18 V bus supply	Request a Quote
750-642	EnOcean radio receiver module, 868.3 MHz, SMA antenna socket, receive only	Request a Quote
750-643	MP-Bus master for Belimo MP-Bus actuators, up to 8 slaves	Request a Quote
750-650	RS-232 C serial interface, 9.6 kBd, 1 TxD / 1 RxD full-duplex	Request a Quote
750-651	TTY serial interface, 20 mA current loop, 1200 ... 19200 baud, full duplex	Request a Quote
750-652	Serial interface RS-232 / RS-422 / RS-485, 300 Bd ... 115.2 kBd	Request a Quote
753-647	DALI multi-master module, DALI-2, 64 control gears + 64 control devices, pluggable	Request a Quote

Intrinsically safe modules

ORDER NUMBER	DESCRIPTION	
750-484	2-channel analog input 4 ... 20 mA HART, intrinsically safe (Ex i), 12 bits	Request a Quote
750-538	2-channel relay output, changeover contacts, 100 VAC / 30 VDC, intrinsically safe (Ex i)	Request a Quote
750-539	4-channel digital output 24 VDC for valves, intrinsically safe (Ex i)	Request a Quote
750-606	Ex i supply module 24 VDC with diagnostics, 1 A output for intrinsically safe segment	Request a Quote
750-633	Up/down counter, 1 counter, 32 bits, 20 Hz ... 50 kHz, 1 DO, intrinsically safe (Ex i)	Request a Quote

Supply, filter and segment modules, end module

ORDER NUMBER	DESCRIPTION	
750-1607	Potential distribution module, 8x 24 V/8x 0 V, 16 connectors, 10 A	Request a Quote

ORDER NUMBER	DESCRIPTION	
750-600	End module for the internal data bus, fixed	Request a Quote
750-601	24 VDC power supply module with fuse holder, power jumper contacts 6.3 A	Request a Quote
750-602	24 VDC power supply module, power jumper contacts 10 A	Request a Quote
750-603	Potential distribution module, 8x 24 V, power jumper contacts 10 A	Request a Quote
750-604	Potential distribution module, 8x 0 V, power jumper contacts 10 A	Request a Quote
750-609	230 VAC power supply module with fuse holder, power jumper contacts 6.3 A	Request a Quote
750-610	24 VDC power supply module with fuse holder and diagnostics, 6.3 A	Request a Quote
750-611	230 VAC power supply module with fuse holder and diagnostics, 6.3 A	Request a Quote
750-612	Power supply module 0 ... 230 VAC/DC, power jumper contacts 10 A	Request a Quote
750-613	System power supply module 24 VDC, 2000 mA system current, power jumper contacts 10 A	Request a Quote
750-614	Potential distribution module 0 ... 230 VAC/DC, power jumper contacts 10 A	Request a Quote
750-615	120 VAC power supply module with fuse holder, power jumper contacts 6.3 A	Request a Quote
750-616	Distance module without power jumper contacts, 12 mm wide	Request a Quote
750-617	24 VAC power supply module with fuse holder, power jumper contacts 6.3 A	Request a Quote
750-621	Distance module with power jumper contacts, 12 mm wide	Request a Quote
750-622	Binary spacer module, 2, 4, 6 or 8 bits, 24 VDC	Request a Quote
750-623	Power supply module 24 VDC in, 5/8/10/12/15 V out via DIP switch	Request a Quote
750-624	Field supply filter (surge) 24 VDC, power jumper contacts 10 A	Request a Quote

Prepared by GEARWELL, 2026-10-14. WAGO, CAGE CLAMP and MULTI CONNECTION SYSTEM are trademarks or registered trademarks of WAGO GmbH & Co. KG. GEARWELL is an independent supplier and is not affiliated with or authorized by WAGO GmbH & Co. KG. Catalog numbers, ratings and specifications are taken from WAGO catalog "WAGO Automation Technology 2026/2", No. 60588173; WAGO manual "750-842 ETHERNET Controller 10 MBit, PLC - ETHERNET TCP/IP Programmable Fieldbus Controller", Version 2.3.0; WAGO manual "750-512 2DO 230V AC 2.0A/ Relay 2NO, 2-Channel Relay Output Module 230 VAC, Non-floating; 2 Make Contacts", Version 1.2.1; WAGO manual "750-519 4 DO DC 5 V 20 mA, High-Side Switching", Version 1.0.4; WAGO manual "750-640 RTC Module", Version 1.0.2; WAGO manual "750-641 DALI/DSI Master Module", Version 1.2.0; WAGO manual "750-642 EnOcean Radio Receiver", Version 1.1.0; WAGO manual "750-651 TTY-Interface 20mA Current Loop", Version 1.0.3. They are given for identification; confirm the full catalog number with the product label before ordering. Official documentation: www.wago.com.